

monty® 3300 racing plus
now certified for handling UHP and run-flat tyres



The gentle and user-friendly
solution, also for
UHP and run-flat tyres

The monty 3300 racing plus was certified; it is now released for handling all UHP and run-flat tyres.

- The monty 3300 racing with pneumatic mounting tool easymont pro has undergone a redesign and is now also certified for the gentle and user-friendly mounting and demounting of UHP and run-flat tyres in line with OEM specifications.
- The innovative triangular bead clamp prevents the tyre from being damaged and retains it in optimum position in the drop centre of the rim.
- The disc demounts the tyre in an especially gentle way, pushing it down in the drop centre of the rim.
- The specially shaped tyre lever levers the bead over the nose of the mounting head without risking any damage.
- Max. outer clamping capability is 24".
- The tyre changer is equipped with a double-acting bead breaking cylinder and a large bead breaker blade to make sure tyres and rims remain undamaged.
- Alloy rims are handled especially gently as mounting head and clamping jaws are provided with plastic protections. In addition the single-part mounting head can be adjusted vertically and laterally in spaced-apart position relative to the rim.
- User-friendliness is ensured thanks to the automatically tilt-back post and the four ergonomic pedals.
- The self-centring four-jaw chuck controlled by two clamping cylinders provides for quick and accurate clamping, exact locking of the post expedites operation even more.

Technical data and standard equipment

Technical data		
Clamping range: inside	inch	14–24
Clamping range: outside	inch	12–24
Rim width	inch	3–14
Max. tyre width	inch	17
Max. wheel diameter	mm	990
Bead breaking range	mm	40–340/140–440
Max. bead breaking range	mm	440
Compressed air supply	bar	8–10
Space requirement (HxWxD)	mm	1950x1350x1650
Weight	kg	320
Power supply	3 / PE AC 380–415 V / 50/60 Hz	
Chuck speed	rpm	7/13

Standard equipment
Tyre lever
Bead clamp
Spacers for bead breaker blade
Plastic rim protection
Plastic tyre protection

Snap-on® Equipment

France

Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP97175
ST Ouen L'Aumone · 95056 Cergy Pontoise Cedex
Phone: +33 (0) 134/48 58-78 · Fax: +33 (0) 134/48 58-70 · www.snapon-equipment.fr

Germany

Snap-on Equipment GmbH – Undercar · Werner-von-Siemens-Str. 2 · 64319 Pfungstadt
Phone: +49 (0) 6157/12-0 · Fax: +49 (0) 6157/12-286 · www.snapon-equipment.de

Italy

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522/733-411 · Fax: +39 0522/733-410

United Kingdom

Snap-on Equipment Ltd. · 48 Sutton Park Avenue · Reading RG6 1AZ
Phone: +44 (0) 118/929-6811 · Fax: +44 (0) 118/966-4369 · www.hofmann.co.uk

EMEA-JA

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)
Phone: +39 0522/733-483 · Fax: +39 0522/733-479 · www.hofmann-ge.com

Part of the machines is illustrated with optional extras available at extra cost.
Technical modifications reserved.