

# *monty® 3300-24 2-speed plus*

Now available  
with clamping  
range of up to 24"



More flexible, innovative,  
and simply better

## monty® 3300-24 2-speed plus

Cars are more and more equipped with bigger wheels so that the specialised garage or tyre shop has an increasing requirement for tyre changers with an extended clamping range.



The new monty 3300-24 2-speed plus exactly meets this requirement. It features sliding jaws and an extended clamping range for wheels of up to 24".

This tyre changer comes standard with the pneumatic mounting tool easymont pro and the plus kit and has been certified by German wdk

for mounting and demounting of UHP and run-flat tyres. Owing to this special equipment the monty 3300-24 2-speed can be used most flexibly for handling wheels and tyres of a wide variety of sizes and types.

- Pneumatic tilt-back post
- Double acting bead breaker cylinder and a large bead breaker blade to prevent rims and tyres from being damaged
- Alloy rims are handled particularly gently as both mounting head and jaws are provided with plastic protectors. In addition the one-part mounting head can be adjusted vertically and horizontally in spaced-apart position relative to the rim.
- The pneumatic tilt-back post and the four ergonomic pedals stand for user-friendly operation.

- Accurate and quick operation is guaranteed owing to the self-centring four-jaw turntable controlled by two clamping cylinders and the exactly locked post.

The machine is also available as monty 3300-24 2-speed without easymont pro and without plus kit (not certified) and in GP version.



The GP version additionally features the external pedal-controlled bead seating device.

Technical data		
Clamping range	inch	outside 10 – 24 / inside 12 – 24
Rim width	inch	3 – 12
Max. tyre width	inch	12
Max. wheel diameter	mm	1000
Bead breaking range	mm	40 – 340
Max. bead breaking range	mm	340
Compressed air supply	bar	8 – 12
Machine dimensions (W x D x H)	mm	1230 x 1340 x 1610
Weight	kg	300
Power supply		3 / PE AC 380 – 415 V / 50 / 60 Hz
Turntable speed	rpm	7 / 13

**Snap-on Equipment**

### France

Snap-on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP97175  
ST Ouen L'Aumone · 95056 Cergy Pontoise Cedex  
Phone: +33 (0) 134/48 58-78 · Fax: +33 (0) 134/48 58-70 · [www.snapon-equipment.fr](http://www.snapon-equipment.fr)

### Germany

Snap-on Equipment GmbH · Werner-von-Siemens-Str. 2 · 64319 Pfungstadt  
Phone: +49 (0) 6157/12-0 · Fax: +49 (0) 6157/12-286 · [www.snapon-equipment.de](http://www.snapon-equipment.de)

### Italy

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)  
Phone: +39 0522/733-411 · Fax: +39 0522/733-410 · [www.snapon-equipment.eu](http://www.snapon-equipment.eu)

### United Kingdom

Snap-on Equipment Ltd. · 48 Sutton Park Avenue · Reading RG6 1AZ  
Phone: +44 (0) 118/929-6811 · Fax: +44 (0) 118/966-4369 · [www.snapon-equipment.co.uk](http://www.snapon-equipment.co.uk)

### EMEA-JA

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE)  
Phone: +39 0522/733-411 · Fax: +39 0522/733-479 · [www.snapon-equipment.eu](http://www.snapon-equipment.eu)

Part of the machines is illustrated with optional extras available at extra cost.  
Technical modifications reserved.

Cod.: 9702 234 · 04/2010